

product information






aluminium garage door system ARK

04/2006



Technical description

Heinzmann-garage door, ready to built in

| | |
|---|---|
|  | <p>shutter container top part and opening are made out of specially formed aluminium sheets.(thickness 1 mm) varnished white, brown or grey, special colours by RAL for surcharge Container at angle of 45°. Sides are made of steel with compressed roll-on system, maintenance-free rolls Octogonal steel shaft 70 mm Ø, galvanized with additional replenishment. from 4000 mm steel-winding shaft 125 mm</p> |
|  | <p>guide rails guide rails 90 mm out of aluminium with hardened vinyl inlay, above bended open funnel-shaped. Type and colour according to container.</p> |
|  | <p>shutter profile aluminium CT 1450, band thickness 0,5 mm, varnished two times, with polyurethane insulation foam core, detention pin screwed, separately packed. Sight and/or ventilation profiles for surcharge. End slat according to container colour with vinyl end slat profile.</p> |
|  | <p>use motor 220 VAC, emergency hand crank for surcharge, downroll security unit with electrical switch-off. Remote control including 2-channel manual transmitter with endslat automatic switch-off system for surcharge.</p> |
|  | <p>security advice: If using remote control unit you have to install an endslat automatic switch-off.</p> |

| Box size mm | max. height (mm) C 2080 |
|-------------|-------------------------|
| 300 | 3000 |
| 360 | 4400 |

| Rail breadth mm | max. breadth (mm) |
|-----------------|-------------------|
| 90 | 5000 |

