

Product information

Vinyl front door „Novum“

12/2005



technical description

	<p>system: Heinzmann-Novum sash 120 mm, frame 85 mm, depth 70 mm, real Three-/Four-chamber-construction with staggered surface</p> <p>material: multi spaced design. Hardened PVC (DIN 7748), frame material group 1 (DIN 4108), exterior wall thickness: 3 mm</p> <p>reinforcement: galvanized reinforcement steel, thickness 3,0 mm, 65 x 45 mm inside sash with welded corner connection.</p> <p>sealings: exterior sealing and interior side panel sealing are made of EPDM and are stuck together. Glass sealing made of EPDM.</p> <p>ground tie: Insulated with extracted mohair-sealing, silver anoded 20 mm for renovation object, for new building connecting profile 43 mm.</p> <p>drainage: Outside drainage according to instructions. Glass fold with additional ventilation.</p>
	<p>colors: white, Standard colors: brown (8875.05), mahagony (2065.021), dark oak (2052.089), golden oak (2178.001), nutbrown (2178.007), special colors for surcharge</p>
	<p>fittings: quality fittings made out of three-times bolt-locking, grey coated, with three stable hinges (adjustable three-dimensional) WK 3 tested; lock with emergency function and three keys. The insertion of the fittings is secured through at least two walls; electric buzzer.</p>
	<p>glazing: tested insulating glass. Lifter in the interior glass-space is welded together. The glass pane is 4/16/4 mm and locks perfectly into the window joint. Strengthened throughout. The simultaneous construction of the whole window insures precision.</p>
	<p>fillings: Glass fiber strengthened vinyl plate material varnished with polyurethane ornament frame and PU-hard foam 90 kg/m³, thickness 24 mm, U-value depending on type 1,3 – 1,8. changeable ornament glasses</p>