

Product information

Vinyl window „classic“

01/2006



Technical description

| | |
|--|---|
| | <p>system: Heinzmann-Classic impact sealing, staggered or flat surface, tested according to RAL RG 716/1 with rounded and intented glass strip.</p> <p>material: multi spaced design. Hardened PVC (DIN 7748), frame material group 1 (DIN 4108), depth 70 mm, exterior wall thickness: 3 mm</p> <p>reinforcement: galvanized reinforcement steel, thickness 1,5 mm, in the frame and side panels on all window sizes.</p> <p>sealings: exterior sealing and interior side panel sealing are made of EPDM and are stuck together. Glass sealing made of EPDM.</p> <p>drainage: Outside drainage according to instructions. Glass fold with additional ventilation.</p> |
| | <p>colors: white, Standard colors: brown (8875.05), mahagony (2065.021), dark oak (2052.089), golden oak (2178.001), nutbrown (2178.007), special colors for surcharge</p> |
| | <p>fittings: Siegenia Favorit SI-Line KF from 650 x 950 mm. The insertion of the fittings is secured through at least two walls (corners and side panelling are secured to the steel). Further burglar protection available for surcharge. Cover caps for fittings on white doors white (on decorative windows and brown doors brown)</p> |
| | <p>glazing: tested insulating glass. Lifter in the interior glass-space is welded together. The glass pane is 4/16/4 mm and locks perfectly into the window joint. Strengthened throughout. The simultaneous construction of the whole window insures precision.</p> |